



MI - 25

Application areas: roads, sports fields


Type: leveler
 Min. required power: 50 HP
 Max required power: 120 HP
 Overall length: 2,80 m
 Overall width: 2,50 m
 Working width: 2,50 m
 Maneuver width: 2,50 m
 Work wheel track: 2,00 m
 Maneuver wheel track: 2,00 m
 Wheels height: 0,84 m
 Blade height: 1,00 m
 Coupling hook hight: 0,45 m
 Estimated weight: 1.300 kg
 Frame design: single frame
 Opening blade system: fix
 Folding blade: no
 Extensible blade: no
 Opening axles system: fix
 Extensible axles: no
 Rear axle: n° 2 indipendent frames
 Pump: n° 2
 Oil filter: cartridge
 Rocker arm (wheels): n° 2 stabilising wheels
 Slope of the blade: hydraulic
 Lights system: yes
 Receiver mast: n° 2 hydraulic extensible
 Earth volume per run: 3 m³
 Finishing speed (km/h): 4 km/h
 Transport distance (m): 80 m
 Laser system: n° 2 hydraulic indipendent
 Ready for laser system: yes
 Ready for GPS system: yes
 Laser system precision on 450 m: ± 2 mm
 GPS system precision on 5 km: ± 10 mm




Overall length




Working width



Maneuver width



Work wheel track



Blade height