



## MMG - 30

Application areas: building, greenhouses and gardening, sports fields


Type: front minigrader  
 Min. required power: 40 HP  
 Max required power: 100 HP  
 Overall length: 1,70 m  
 Overall width: 3,00 m  
 Working width: 3,00 m  
 Maneuver width: 2,30 m  
 Work wheel track: 1,40 m  
 Maneuver wheel track: 1,20 m  
 Wheels height: 0,40 m  
 Blade height: 0,65 m  
 Estimated weight: 500 kg  
 Frame design: single frame  
 Opening blade system: fix  
 Folding blade: no  
 Extensible blade: no  
 Opening axles system: fix  
 Extensible axles: no  
 Front bogie: n° 2 pivoting wheels  
 Slope of the blade: hydraulic 20°  
 Blade angle: hydraulic 25°  
 Adjustable attack angle: yes (through front loader)  
 Lights system: optional  
 Receiver mast: n° 2 manual extensible  
 Earth volume per run: 1,5 m<sup>3</sup>  
 Finishing speed (km/h): 3 km/h  
 Transport distance (m): 40 m  
 Laser system: hydraulic interface group  
 Ready for laser system: yes  
 Ready for GPS system: yes  
 Laser system precision on 450 m: ± 2 mm  
 GPS system precision on 5 km: ± 10 mm




Overall length




Working width



Maneuver width



Work wheel track



Blade height