



MNG - 21.26

Application areas: building, sports fields

Type: front minigrader extensible blade
 Min. required power: 40 HP
 Max required power: 100 HP
 Overall length: 1,80 m
 Overall width: 2,60 m
 Working width: 2,10 m – 2,60 m
 Maneuver width: 1,60 m
 Work wheel track: 1,40 m
 Maneuver wheel track: 1,20 m
 Wheels height: 0,40 m
 Blade height: 0,65 m
 Estimated weight: 530 kg
 Frame design: single frame
 Opening blade system: hydraulic
 Folding blade: no
 Extensible blade: yes
 Opening axles system: fix
 Extensible axles: no
 Front bogie: n° 2 pivoting wheels
 Slope of the blade: hydraulic 20°
 Blade angle: hydraulic 25°
 Adjustable attack angle: yes (through front loader)
 Lights system: optional
 Receiver mast: n° 2 manual extensible
 Earth volume per run: 1,4 m³
 Finishing speed (km/h): 3 km/h
 Transport distance (m): 40 m
 Laser system: hydraulic interface group
 Ready for laser system: yes
 Ready for GPS system: yes
 Laser system precision on 450 m: ± 2 mm
 GPS system precision on 5 km: ± 10 mm




Overall length




Working width



Maneuver width



Work wheel track



Blade height